



**LORK INDUSTRIAS, S.L.**  
 CARACAS, 11  
 08030—BARCELONA  
 SPAIN  
 Tel: 0034 93 346 82 12  
 Fax: 0034 93 311 30 60  
 Email: lork@lorkindustrias.com

## Barras - PA6G

<b>Ø</b>	<b>Tolerancia</b>	<b>Peso</b>	<b>Longitud</b>		
			<b>1000 mm</b>	<b>2000 mm</b>	<b>3000 mm</b>
20	+ 0,7 + 0,2	0,37	●	●	●
22	+ 0,9 + 0,2	0,46	○	○	○
25	+ 0,9 + 0,2	0,60	●	●	●
28	+ 0,9 + 0,2	0,75	○	○	○
30	+ 0,9 + 0,2	0,85	●	●	●
32	+ 1,1 + 0,2	1,00	○	○	○
35	+ 1,1 + 0,2	1,20	●	●	●
40	+ 1,1 + 0,2	1,50	●	●	●
45	+ 1,3 + 0,3	1,90	●	●	●
50	+ 1,3 + 0,3	2,40	●	●	●
55	+ 1,3 + 0,3	2,80	●	●	●
60	+ 1,6 + 0,3	3,40	●	●	●
65	+ 1,6 + 0,3	4,00	●	●	●
70	+ 1,6 + 0,3	4,80	●	●	●
75	+ 3,0 + 0,4	5,40	●	●	●
80	+ 3,0 + 0,4	6,0	●	●	●
85	+ 3,0 + 0,4	6,8	●	●	●
90	+ 3,0 + 0,4	7,7	●	●	●
95	+ 3,0 + 0,4	8,6	●	●	●
100	+ 3,0 + 0,4	9,6	●	●	●
110	+ 5,0 + 1,5	11,6	●	●	●
115	+ 5,0 + 1,5	12,7	●	●	●
120	+ 5,0 + 1,5	13,8	●	●	●
125	+ 5,0 + 1,5	14,8	●	●	●
130	+ 5,0 + 1,5	16,5	●	●	●
135	+ 5,0 + 1,5	18,0	●	●	●
140	+ 5,0 + 1,5	19,1	●	●	●
145	+ 5,0 + 1,5	20,3	●	●	●
150	+ 5,0 + 1,5	21,6	●	●	●

- Medida habitualmente en stock
- Fabricación bajo pedido

**PESOS ORIENTATIVOS**

**LORK INDUSTRIAS, S.L.**

CARACAS, 11

08030—BARCELONA

SPAIN

Tel: 0034 93 346 82 12

Fax: 0034 93 311 30 60

Email: lork@lorkindustrias.com

## Barras - PA6G

<b>Ø</b>	<b>Tolerancia</b>	<b>Peso</b>	<b>Longitud</b>
<b>mm</b>	<b>mm</b>	<b>kgs/m</b>	<b>1000 mm</b>
155	+ 5,0 + 1,5	23,5	●
160	+ 7,0 + 2,0	24,7	●
165	+ 7,0 + 2,0	26,5	●
170	+ 7,0 + 2,0	28,0	●
175	+ 7,0 + 2,0	30,2	●
180	+ 7,0 + 2,0	31,5	●
190	+ 7,0 + 2,0	34,5	●
200	+ 7,0 + 2,0	38,0	●
210	+ 9,0 + 2,0	42,5	○
220	+ 9,0 + 2,0	46,5	●
230	+ 9,0 + 2,0	50,5	●
240	+ 9,0 + 2,0	55,0	○
250	+ 9,0 + 2,0	59,8	●
260	+ 9,0 + 2,0	64,0	○
270	+ 9,0 + 2,0	69,6	○
280	+ 9,0 + 2,0	74,5	●
290	+ 9,0 + 2,0	80,0	○
300	+ 9,0 + 2,0	85,5	●
310	+ 11,0 + 3,0	91,0	○
320	+ 11,0 + 3,0	98,0	●
330	+ 11,0 + 3,0	104,0	○
340	+ 11,0 + 3,0	112,0	○
350	+ 11,0 + 3,0	117,0	●
360	+ 11,0 + 3,0	124,0	○
370	+ 11,0 + 3,0	132,0	○
380	+ 11,0 + 3,0	138,0	○
390	+ 11,0 + 3,0	145,0	○
400	+ 11,0 + 3,0	153,0	●

<b>Ø</b>	<b>Tolerancia</b>		<b>Peso</b>	<b>Longitud</b>	
<b>mm</b>	<b>mm</b>		<b>kgs/m</b>	<b>1000 mm</b>	<b>500 mm</b>
410	+ 13	+ 4,0	162,0	○	
420	+ 13	+ 4,0	170,0	○	
430	+ 13	+ 4,0	178,0	○	
440	+ 13	+ 4,0	185,0	○	
450	+ 13	+ 4,0	196,0	○	
460	+ 13	+ 4,0	202,0	○	
470	+ 13	+ 4,0	212,0	○	
480	+ 13	+ 4,0	222,0	○	
490	+ 13	+ 4,0	230,0	○	
500	+ 13	+ 4,0	243,0	○	
510	+ 15	+ 5,0	254,0		○
520	+ 15	+ 5,0	261,0		○
530	+ 15	+ 5,0	273,0		○
540	+ 15	+ 5,0	284,0		○
550	+ 15	+ 5,0	301,0		○
560	+ 15	+ 5,0	309,0		○
570	+ 15	+ 5,0	323,0		○
580	+ 15	+ 5,0	329,0		○
590	+ 15	+ 5,0	343,0		○
600	+ 15	+ 5,0	352,0		○
610	+ 15	+ 5,0	361,0		○
620	+ 15	+ 5,0	374,0		○
625	+ 15	+ 5,0	377,0		○
630	+ 15	+ 5,0	386,0		○
640	+ 15	+ 5,0	397,0		○
650	+ 15	+ 5,0	415,0		○
660	+ 15	+ 5,0	425,0		○
670	+ 15	+ 5,0	441,0		○
680	+ 15	+ 5,0	451,0		○
690	+ 15	+ 5,0	468,0		○
700	+ 15	+ 5,0	488,0		○
710	+ 15	+ 5,0	501,0		○

- Medida habitualmente en stock
- Fabricación bajo pedido

**PESOS ORIENTATIVOS**